

gnutls\_global\_set\_audit\_log\_function(3)            gnutls            gnutls\_global\_set\_audit\_log\_function(3)

## NAME

gnutls\_global\_set\_audit\_log\_function - API function

## SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_global_set_audit_log_function(gnutls_audit_log_func log_func);
```

## ARGUMENTS

gnutls\_audit\_log\_func log\_func  
it is the audit log function

## DESCRIPTION

This is the function to set the audit logging function. This is a function to report important issues, such as possible attacks in the protocol. This is different from **gnutls\_global\_set\_log\_function()** because it will report also session-specific events. The session parameter will be null if there is no corresponding TLS session.

*gnutls\_audit\_log\_func* is of the form, void (\*gnutls\_audit\_log\_func)( gnutls\_session\_t, const char\*);

## SINCE

3.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>