

NAME

gnutls_ocsp_req_print - API function

SYNOPSIS

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_req_print(gnutls_ocsp_req_const_t req, gnutls_ocsp_print_formats_t format,  
gnutls_datum_t * out);
```

ARGUMENTS

gnutls_ocsp_req_const_t req

The data to be printed

gnutls_ocsp_print_formats_t format

Indicate the format to use

gnutls_datum_t * out

Newly allocated datum with (0) terminated string.

DESCRIPTION

This function will pretty print a OCSP request, suitable for display to a human.

If the format is **GNUTLS_OCSP_PRINT_FULL** then all fields of the request will be output, on multiple lines.

The output *out* ->data needs to be deallocate using **gnutls_free()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>