

NAME

gnutls_ocsp_req_set_nonce - API function

SYNOPSIS

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_req_set_nonce(gnutls_ocsp_req_t req, unsigned int critical, const gnutls_datum_t *
nonce);
```

ARGUMENTS

gnutls_ocsp_req_t req
should contain a **gnutls_ocsp_req_t** type

unsigned int critical
critical flag, normally false.

const gnutls_datum_t * nonce
the nonce data

DESCRIPTION

This function will add an nonce extension to the OCSP request. Calling this function multiple times will overwrite values from earlier calls.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_ocsp_req_set_nonce(3)

gnutls

gnutls_ocsp_req_set_nonce(3)

<https://www.gnutls.org/manual/>