

NAME

gnutls_ocsp_resp_get_nonce - API function

SYNOPSIS

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_resp_get_nonce(gnutls_ocsp_resp_const_t resp, unsigned int * critical, gnutls_datum_t * nonce);
```

ARGUMENTS

gnutls_ocsp_resp_const_t resp

should contain a **gnutls_ocsp_resp_t** type

unsigned int * critical

whether nonce extension is marked critical

gnutls_datum_t * nonce

will hold newly allocated buffer with nonce data

DESCRIPTION

This function will return the Basic OCSP Response nonce extension data.

The caller needs to deallocate memory by calling **gnutls_free()** on *nonce* ->data.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>