

NAME

gnutls_ocsp_resp_import - API function

SYNOPSIS

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_resp_import(gnutls_ocsp_resp_t resp, const gnutls_datum_t * data);
```

ARGUMENTS

gnutls_ocsp_resp_t resp

The data to store the parsed response.

const gnutls_datum_t * data

DER encoded OCSP response.

DESCRIPTION

This function will convert the given DER encoded OCSP response to the native **gnutls_ocsp_resp_t** format. It also decodes the Basic OCSP Response part, if any. The output will be stored in *resp*.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>