

**NAME**

gnutls\_ocsp\_resp\_import2 - API function

**SYNOPSIS**

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_resp_import2(gnutls_ocsp_resp_t resp, const gnutls_datum_t * data,  
gnutls_x509_cert_fmt_t fmt);
```

**ARGUMENTS**

gnutls\_ocsp\_resp\_t resp

The data to store the parsed response.

const gnutls\_datum\_t \* data

DER or PEM encoded OCSP response.

gnutls\_x509\_cert\_fmt\_t fmt

DER or PEM

**DESCRIPTION**

This function will convert the given OCSP response to the native **gnutls\_ocsp\_resp\_t** format. It also decodes the Basic OCSP Response part, if any. The output will be stored in *resp*.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

3.6.3

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>