

gnutls_ocsp_status_request_enable_client(3) gnutls gnutls_ocsp_status_request_enable_client(3)

NAME

gnutls_ocsp_status_request_enable_client - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_ocsp_status_request_enable_client(gnutls_session_t session, gnutls_datum_t * responder_id,
size_t responder_id_size, gnutls_datum_t * extensions);
```

ARGUMENTS

gnutls_session_t session
is a **gnutls_session_t** type.

gnutls_datum_t * responder_id
ignored, must be **NULL**

size_t responder_id_size
ignored, must be zero

gnutls_datum_t * extensions
ignored, must be **NULL**

DESCRIPTION

This function is to be used by clients to request OCSP response from the server, using the "status_request" TLS extension. Only OCSP status type is supported.

Previous versions of GnuTLS supported setting *responder_id* and *extensions* fields, but due to the difficult semantics of the parameter usage, and other issues, this support was removed since 3.6.0 and these parameters must be set to **NULL**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

SINCE

3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

gnutls_ocsp_status_request_enable_client(3) gnutls gnutls_ocsp_status_request_enable_client(3)

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>