

NAME

gnutls_ocsp_status_request_get - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_ocsp_status_request_get(gnutls_session_t session, gnutls_datum_t * response);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

gnutls_datum_t * response

a **gnutls_datum_t** with DER encoded OCSP response

DESCRIPTION

This function returns the OCSP status response received from the TLS server. The *response* should be treated as constant. If no OCSP response is available then

GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE is returned.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

SINCE

3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_ocsp_status_request_get(3)

gnutls

gnutls_ocsp_status_request_get(3)

<https://www.gnutls.org/manual/>