

NAME

gnutls_ocsp_status_request_get2 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_ocsp_status_request_get2(gnutls_session_t session, unsigned idx, gnutls_datum_t *
response);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

unsigned idx the index of peer's certificate

gnutls_datum_t * response

a **gnutls_datum_t** with DER encoded OCSP response

DESCRIPTION

This function returns the OCSP status response received from the TLS server for the certificate index provided. The index corresponds to certificates as returned by `gnutls_certificate_get_peers`. When index is zero this function operates identically to **gnutls_ocsp_status_request_get()**.

The returned *response* should be treated as constant. If no OCSP response is available for the given index then **GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE** is returned.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

SINCE

3.6.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>