

NAME

gnutls_pcert_import_openpgp_raw - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pcert_import_openpgp_raw(gnutls_pcert_st * pcert, const gnutls_datum_t * cert,  
gnutls_openpgp_cert_fmt_t    format, gnutls_openpgp_keyid_t keyid, unsigned int flags);
```

ARGUMENTS

gnutls_pcert_st * pcert

The pcert structure

const gnutls_datum_t * cert

The raw certificate to be imported

gnutls_openpgp_cert_fmt_t format

The format of the certificate

gnutls_openpgp_keyid_t keyid

The key ID to use (NULL for the master key)

unsigned int flags

zero for now

DESCRIPTION

This function is no-op.

RETURNS

GNUTLS_E_UNIMPLEMENTED_FEATURE.

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>