

NAME

gnutls_pcert_import_rawpk - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pcert_import_rawpk(gnutls_pcert_st *pcert, gnutls_pubkey_t pubkey, unsigned int flags);
```

ARGUMENTS

gnutls_pcert_st *pcert

The pcert structure to import the data into.

gnutls_pubkey_t pubkey

The raw public-key in **gnutls_pubkey_t** format to be imported

unsigned int flags

zero for now

DESCRIPTION

This convenience function will import (i.e. convert) the given raw public key *pubkey* into a **gnutls_pcert_st** structure. The structure must be deinitialized afterwards using **gnutls_pcert_deinit()**. The given *pubkey* must not be deinitialized because it will be associated with the given *pcert* structure and will be deinitialized with it.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.6.6

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>