

NAME

gnutls_pcert_import_x509_raw - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pcert_import_x509_raw(gnutls_pcert_st * pcert, const gnutls_datum_t * cert,  
gnutls_x509_crt_fmt_t format, unsigned int flags);
```

ARGUMENTS

gnutls_pcert_st * pcert

The pcert structure

const gnutls_datum_t * cert

The raw certificate to be imported

gnutls_x509_crt_fmt_t format

The format of the certificate

unsigned int flags

zero for now

DESCRIPTION

This convenience function will import the given certificate to a **gnutls_pcert_st** structure. The structure must be deinitialized afterwards using **gnutls_pcert_deinit()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>