

NAME

gnutls_pkcs11_copy_secret_key - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_copy_secret_key(const char * token_url, gnutls_datum_t * key, const char * label,
unsigned int key_usage, unsigned int flags);
```

ARGUMENTS

const char * token_url

A PKCS **11** URL specifying a token

gnutls_datum_t * key

The raw key

const char * label

A name to be used for the stored data

unsigned int key_usage

One of GNUTLS_KEY_*

unsigned int flags

One of GNUTLS_PKCS11_OBJ_FLAG_*

DESCRIPTION

This function will copy a raw secret (symmetric) key into a PKCS **11** token specified by a URL. The key can be marked as sensitive or not.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>