

NAME

gnutls_pkcs11_obj_get_flags - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_obj_get_flags(gnutls_pkcs11_obj_t obj, unsigned int * oflags);
```

ARGUMENTS

gnutls_pkcs11_obj_t obj
The pkcs11 object

unsigned int * oflags
Will hold the output flags

DESCRIPTION

This function will return the flags of the object. The *oflags* will be flags from **gnutls_pkcs11_obj_flags**. That is, the **GNUTLS_PKCS11_OBJ_FLAG_MARK_*** flags.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.7

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>