

NAME

gnutls_pkcs11_token_get_flags - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_token_get_flags(const char * url, unsigned int * flags);
```

ARGUMENTS

const char * url

should contain a PKCS 11 URL

unsigned int * flags

The output flags (GNUTLS_PKCS11_TOKEN_*)

DESCRIPTION

This function will return information about the PKCS 11 token flags.

The supported flags are: **GNUTLS_PKCS11_TOKEN_HW** and **GNUTLS_PKCS11_TOKEN_TRUSTED**.

RETURNS

GNUTLS_E_SUCCESS (0) on success or a negative error code on error.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>