

NAME

gnutls_pkcs11_token_get_mechanism - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_token_get_mechanism(const char * url, unsigned int idx, unsigned long *  
mechanism);
```

ARGUMENTS

const char * url

should contain a PKCS 11 URL

unsigned int idx

The index of the mechanism

unsigned long * mechanism

The PKCS 11 mechanism ID

DESCRIPTION

This function will return the names of the supported mechanisms by the token. It should be called with an increasing index until it return GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE.

RETURNS

GNUTLS_E_SUCCESS (0) on success or a negative error code on error.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>