

NAME

gnutls_pkcs11_token_get_url - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_token_get_url(unsigned int seq, gnutls_pkcs11_url_type_t detailed, char ** url);
```

ARGUMENTS

unsigned int seq

sequence number starting from 0

gnutls_pkcs11_url_type_t detailed

non zero if a detailed URL is required

char ** url will contain an allocated url

DESCRIPTION

This function will return the URL for each token available in system. The url has to be released using **gnutls_free()**

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned,

GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE if the sequence number exceeds the available tokens, otherwise a negative error value.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>