

NAME

gnutls_pkcs11_token_set_pin - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_token_set_pin(const char * token_url, const char * oldpin, const char * newpin,  
unsigned int flags);
```

ARGUMENTS

const char * token_url
A PKCS **11** URL specifying a token

const char * oldpin
old user's PIN

const char * newpin
new user's PIN

unsigned int flags
one of **gnutls_pin_flag_t**.

DESCRIPTION

This function will modify or set a user or administrator's PIN for the given token. If it is called to set a PIN for first time the oldpin must be **NULL**. When setting the admin's PIN with the **GNUTLS_PIN_SO** flag, the *oldpin* value must be provided (this requirement is relaxed after GnuTLS 3.6.5 since which the PIN will be requested if missing).

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>