

NAME

gnutls_pkcs12_bag_get_key_id - API function

SYNOPSIS

```
#include <gnutls/pkcs12.h>
```

```
int gnutls_pkcs12_bag_get_key_id(gnutls_pkcs12_bag_t bag, unsigned indx, gnutls_datum_t * id);
```

ARGUMENTS

gnutls_pkcs12_bag_t bag

The bag

unsigned indx The bag's element to add the id

gnutls_datum_t * id

where the ID will be copied (to be treated as const)

DESCRIPTION

This function will return the key ID, of the specified bag element. The key ID is usually used to distinguish the local private key and the certificate pair.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value, or a negative error code on error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>