

gnutls_pkcs12_bag_set_friendly_name(3) gnutls gnutls_pkcs12_bag_set_friendly_name(3)

NAME

gnutls_pkcs12_bag_set_friendly_name - API function

SYNOPSIS

```
#include <gnutls/pkcs12.h>
```

```
int gnutls_pkcs12_bag_set_friendly_name(gnutls_pkcs12_bag_t bag, unsigned indx, const char * name);
```

ARGUMENTS

gnutls_pkcs12_bag_t bag

The bag

unsigned indx The bag's element to add the id

const char * name

the name

DESCRIPTION

This function will add the given key friendly name, to the specified, by the index, bag element. The name will be encoded as a 'Friendly name' bag attribute, which is usually used to set a user name to the local private key and the certificate pair.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value. or a negative error code on error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_pkcs12_bag_set_friendly_name(3)

gnutls

gnutls_pkcs12_bag_set_friendly_name(3)

<https://www.gnutls.org/manual/>