

NAME

gnutls_pkcs12_export2 - API function

SYNOPSIS

```
#include <gnutls/pkcs12.h>
```

```
int gnutls_pkcs12_export2(gnutls_pkcs12_t pkcs12, gnutls_x509_cert_fmt_t format, gnutls_datum_t *  
out);
```

ARGUMENTS

gnutls_pkcs12_t *pkcs12*

A pkcs12 type

gnutls_x509_cert_fmt_t *format*

the format of output params. One of PEM or DER.

gnutls_datum_t * *out*

will contain a structure PEM or DER encoded

DESCRIPTION

This function will export the pkcs12 structure to DER or PEM format.

The output buffer is allocated using **gnutls_malloc()**.

If the structure is PEM encoded, it will have a header of "BEGIN PKCS12".

RETURNS

In case of failure a negative error code will be returned, and 0 on success.

SINCE

3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>