

**NAME**

gnutls\_pkcs12\_get\_bag - API function

**SYNOPSIS**

```
#include <gnutls/pkcs12.h>
```

```
int gnutls_pkcs12_get_bag(gnutls_pkcs12_t pkcs12, int indx, gnutls_pkcs12_bag_t bag);
```

**ARGUMENTS**

gnutls\_pkcs12\_t pkcs12

A pkcs12 type

int indx        contains the index of the bag to extract

gnutls\_pkcs12\_bag\_t bag

An initialized bag, where the contents of the bag will be copied

**DESCRIPTION**

This function will return a Bag from the PKCS12 structure.

After the last Bag has been read **GNUTLS\_E\_REQUESTED\_DATA\_NOT\_AVAILABLE** will be returned.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>