

NAME

gnutls_pkcs7_export2 - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_export2(gnutls_pkcs7_t pkcs7, gnutls_x509_cert_fmt_t format, gnutls_datum_t * out);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7
The pkcs7 type

gnutls_x509_cert_fmt_t format
the format of output params. One of PEM or DER.

gnutls_datum_t * out
will contain a structure PEM or DER encoded

DESCRIPTION

This function will export the pkcs7 structure to DER or PEM format.

The output buffer is allocated using **gnutls_malloc()**.

If the structure is PEM encoded, it will have a header of "BEGIN PKCS7".

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>