

NAME

gnutls_pkcs7_get_crl_raw2 - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_get_crl_raw2(gnutls_pkcs7_t pkcs7, unsigned indx, gnutls_datum_t *crl);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7

The pkcs7 type

unsigned indx contains the index of the crl to extract

gnutls_datum_t *crl

will contain the contents of the CRL in an allocated buffer

DESCRIPTION

This function will return a DER encoded CRL of the PKCS7 or RFC2630 crl set.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value. After the last crl has been read **GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE** will be returned.

SINCE

3.4.2

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>