

NAME

gnutls_pkcs7_get_cert_raw - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_get_cert_raw(gnutls_pkcs7_t pkcs7, unsigned indx, void * certificate, size_t *  
certificate_size);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7

should contain a gnutls_pkcs7_t type

unsigned indx contains the index of the certificate to extract

void * certificate

the contents of the certificate will be copied there (may be null)

size_t * certificate_size

should hold the size of the certificate

DESCRIPTION

This function will return a certificate of the PKCS7 or RFC2630 certificate set.

After the last certificate has been read **GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE** will be returned.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value. If the provided buffer is not long enough, then *certificate_size* is updated and **GNUTLS_E_SHORT_MEMORY_BUFFER** is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>