

gnutls_pkcs7_get_embedded_data_oid(3) gnutls gnutls_pkcs7_get_embedded_data_oid(3)

NAME

gnutls_pkcs7_get_embedded_data_oid - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
const char * gnutls_pkcs7_get_embedded_data_oid(gnutls_pkcs7_t pkcs7);
```

ARGUMENTS

gnutls_pkcs7_t *pkcs7*
should contain a gnutls_pkcs7_t type

DESCRIPTION

This function will return the OID of the data embedded in the signature of the PKCS7 structure. If no data are available then **NULL** will be returned. The returned value will be valid during the lifetime of the *pkcs7* structure.

RETURNS

On success, a pointer to an OID string, **NULL** on error.

SINCE

3.5.5

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>