

NAME

gnutls_pkcs7_set_cert - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_set_cert(gnutls_pkcs7_t pkcs7, gnutls_x509_cert_t crt);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7
The pkcs7 type

gnutls_x509_cert_t crt
the certificate to be copied.

DESCRIPTION

This function will add a parsed certificate to the PKCS7 or RFC2630 certificate set. This is a wrapper function over **gnutls_pkcs7_set_cert_raw()** .

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>