

NAME

gnutls_pkcs7_sign - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_sign(gnutls_pkcs7_t pkcs7, gnutls_x509_cert_t signer, gnutls_privkey_t signer_key,  
const gnutls_datum_t * data, gnutls_pkcs7_attrs_t signed_attrs, gnutls_pkcs7_attrs_t unsigned_attrs,  
gnutls_digest_algorithm_t dig, unsigned flags);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7

should contain a **gnutls_pkcs7_t** type

gnutls_x509_cert_t signer

the certificate to sign the structure

gnutls_privkey_t signer_key

the key to sign the structure

const gnutls_datum_t * data

The data to be signed or **NULL** if the data are already embedded

gnutls_pkcs7_attrs_t signed_attrs

Any additional attributes to be included in the signed ones (or **NULL**)

gnutls_pkcs7_attrs_t unsigned_attrs

Any additional attributes to be included in the unsigned ones (or **NULL**)

gnutls_digest_algorithm_t dig

The digest algorithm to use for signing

unsigned flags

Should be zero or one of **GNUTLS_PKCS7** flags

DESCRIPTION

This function will add a signature in the provided PKCS 7 structure for the provided data. Multiple signatures can be made with different signers.

The available flags are: **GNUTLS_PKCS7_EMBED_DATA**, **GNUTLS_PKCS7_INCLUDE_TIME**,

GNUTLS_PKCS7_INCLUDE_CERT, and **GNUTLS_PKCS7_WRITE_SPKI**. They are explained in the **gnutls_pkcs7_sign_flags** definition.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.4.2

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>