

NAME

gnutls_priority_string_list - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
const char * gnutls_priority_string_list(unsigned iter, unsigned int flags);
```

ARGUMENTS

unsigned *iter* an integer counter starting from zero

unsigned int *flags*

one of **GNUTLS_PRIORITY_LIST_INIT_KEYWORDS**,
GNUTLS_PRIORITY_LIST_SPECIAL

DESCRIPTION

Can be used to iterate all available priority strings. Due to internal implementation details, there are cases where this function can return the empty string. In that case that string should be ignored. When no strings are available it returns **NULL**.

RETURNS

a priority string

SINCE

3.4.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_priority_string_list(3)

gnutls

gnutls_priority_string_list(3)

<https://www.gnutls.org/manual/>