

NAME

gnutls_privkey_export_pkcs11 - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_privkey_export_pkcs11(gnutls_privkey_t pkey, gnutls_pkcs11_privkey_t * key);
```

ARGUMENTS

gnutls_privkey_t *pkey*

The private key

gnutls_pkcs11_privkey_t * *key*

Location for the key to be exported.

DESCRIPTION

Converts the given abstract private key to a **gnutls_pkcs11_privkey_t** type. The key must be of type **GNUTLS_PRIVKEY_PKCS11**. The key returned in *key* must be deinitialized with **gnutls_pkcs11_privkey_deinit()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.4.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>