

**NAME**

gnutls\_privkey\_import\_pkcs11 - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_privkey_import_pkcs11(gnutls_privkey_t pkey, gnutls_pkcs11_privkey_t key, unsigned int flags);
```

**ARGUMENTS**

gnutls\_privkey\_t pkey

The private key

gnutls\_pkcs11\_privkey\_t key

The private key to be imported

unsigned int flags

Flags for the import

**DESCRIPTION**

This function will import the given private key to the abstract **gnutls\_privkey\_t** type.

The **gnutls\_pkcs11\_privkey\_t** object must not be deallocated during the lifetime of this structure.

*flags* might be zero or one of **GNUTLS\_PRIVKEY\_IMPORT\_AUTO\_RELEASE** and **GNUTLS\_PRIVKEY\_IMPORT\_COPY**.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

2.12.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>