

**NAME**

gnutls\_privkey\_import\_tpm\_url - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_privkey_import_tpm_url(gnutls_privkey_t pkey, const char * url, const char * srk_password,  
const char * key_password, unsigned int flags);
```

**ARGUMENTS**

gnutls\_privkey\_t pkey

The private key

const char \* url

The URL of the TPM key to be imported

const char \* srk\_password

The password for the SRK key (optional)

const char \* key\_password

A password for the key (optional)

unsigned int flags

One of the GNUTLS\_PRIVKEY\_\* flags

**DESCRIPTION**

This function will import the given private key to the abstract **gnutls\_privkey\_t** type.

Note that unless **GNUTLS\_PRIVKEY\_DISABLE\_CALLBACKS** is specified, if incorrect (or NULL) passwords are given the PKCS11 callback functions will be used to obtain the correct passwords.

Otherwise if the SRK password is wrong **GNUTLS\_E\_TPM\_SRK\_PASSWORD\_ERROR** is returned and if the key password is wrong or not provided then

**GNUTLS\_E\_TPM\_KEY\_PASSWORD\_ERROR** is returned.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

3.1.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>