

**NAME**

gnutls\_privkey\_set\_flags - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
void gnutls_privkey_set_flags(gnutls_privkey_t key, unsigned int flags);
```

**ARGUMENTS**

gnutls\_privkey\_t key

A key of type **gnutls\_privkey\_t**

unsigned int flags

flags from the **gnutls\_privkey\_flags**

**DESCRIPTION**

This function will set flags for the specified private key, after it is generated. Currently this is useful for the **GNUTLS\_PRIVKEY\_FLAG\_EXPORT\_COMPAT** to allow exporting a "provable" private key in backwards compatible way.

**SINCE**

3.5.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>