

gnutls_psk_set_client_credentials_function2(3) gnutls gnutls_psk_set_client_credentials_function2(3)

NAME

gnutls_psk_set_client_credentials_function2 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_psk_set_client_credentials_function2(gnutls_psk_client_credentials_t cred,  
gnutls_psk_client_credentials_function2 *func);
```

ARGUMENTS

gnutls_psk_client_credentials_t cred
is a **gnutls_psk_server_credentials_t** type.

gnutls_psk_client_credentials_function2 * func
is the callback function

DESCRIPTION

This function can be used to set a callback to retrieve the username and password for client PSK authentication. The callback's function form is: `int (*callback)(gnutls_session_t, gnutls_datum_t* username, gnutls_datum_t* key);`

This callback function has the same semantics as that of **gnutls_psk_set_client_credentials_function()**, but it allows non-string usernames to be used.

The *username* and *key* ->data must be allocated using **gnutls_malloc()**. The *username* should be an ASCII string or UTF-8 string. In case of a UTF-8 string it is recommended to be following the PRECIS framework for usernames (rfc8265).

The callback function will be called once per handshake.

The callback function should return 0 on success. -1 indicates an error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

gnutls_psk_set_client_credentials_function2(3) gnutls gnutls_psk_set_client_credentials_function2(3)

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>