

gnutls_psk_set_server_credentials_function(3) gnutls gnutls_psk_set_server_credentials_function(3)

NAME

gnutls_psk_set_server_credentials_function - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_psk_set_server_credentials_function(gnutls_psk_server_credentials_t cred,  
gnutls_psk_server_credentials_function *func);
```

ARGUMENTS

gnutls_psk_server_credentials_t cred
is a **gnutls_psk_server_credentials_t** type.

gnutls_psk_server_credentials_function * func
is the callback function

DESCRIPTION

This function can be used to set a callback to retrieve the user's PSK credentials. The callback's function form is: `int (*callback)(gnutls_session_t, const char* username, gnutls_datum_t* key);`

username contains the actual username. The *key* must be filled in using the **gnutls_malloc()**.

In case the callback returned a negative number then gnutls will assume that the username does not exist.

The callback function will only be called once per handshake. The callback function should return 0 on success, while -1 indicates an error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/`

gnutls_psk_set_server_credentials_function(3) gnutls gnutls_psk_set_server_credentials_function(3)

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>