

gnutls\_psk\_set\_server\_credentials\_hint(3)          gnutls          gnutls\_psk\_set\_server\_credentials\_hint(3)

## NAME

gnutls\_psk\_set\_server\_credentials\_hint - API function

## SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_psk_set_server_credentials_hint(gnutls_psk_server_credentials_t res, const char * hint);
```

## ARGUMENTS

gnutls\_psk\_server\_credentials\_t res  
is a **gnutls\_psk\_server\_credentials\_t** type.

const char \* hint  
is the PSK identity hint string

## DESCRIPTION

This function sets the identity hint, in a **gnutls\_psk\_server\_credentials\_t** type. This hint is sent to the client to help it chose a good PSK credential (i.e., username and password).

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise an error code is returned.

## SINCE

2.4.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>