

NAME

`gnutls_psk_set_server_params_function` - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_psk_set_server_params_function(gnutls_psk_server_credentials_t res,
                                           gnutls_params_function * func);
```

ARGUMENTS

`gnutls_psk_server_credentials_t res`
is a `gnutls_certificate_credentials_t` type

`gnutls_params_function * func`
is the function to be called

DESCRIPTION

This function will set a callback in order for the server to get the Diffie-Hellman parameters for PSK authentication. The callback should return **GNUTLS_E_SUCCESS** (0) on success.

DEPRECATED

This function is unnecessary and discouraged on GnuTLS 3.6.0 or later. Since 3.6.0, DH parameters are negotiated following RFC7919.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>. Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>