

NAME

gnutls_pubkey_export2 - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_export2(gnutls_pubkey_t key, gnutls_x509_crt_fmt_t format, gnutls_datum_t *
out);
```

ARGUMENTS

gnutls_pubkey_t key

Holds the certificate

gnutls_x509_crt_fmt_t format

the format of output params. One of PEM or DER.

gnutls_datum_t * out

will contain a certificate PEM or DER encoded

DESCRIPTION

This function will export the public key to DER or PEM format. The contents of the exported data is the SubjectPublicKeyInfo X.509 structure.

The output buffer will be allocated using **gnutls_malloc()**.

If the structure is PEM encoded, it will have a header of "BEGIN CERTIFICATE".

RETURNS

In case of failure a negative error code will be returned, and 0 on success.

SINCE

3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>