

**NAME**

gnutls\_pubkey\_export\_dsa\_raw - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_export_dsa_raw(gnutls_pubkey_t key, gnutls_datum_t * p, gnutls_datum_t * q,  
gnutls_datum_t * g, gnutls_datum_t * y);
```

**ARGUMENTS**

gnutls\_pubkey\_t key

Holds the public key

gnutls\_datum\_t \* p

will hold the p (may be **NULL**)

gnutls\_datum\_t \* q

will hold the q (may be **NULL**)

gnutls\_datum\_t \* g

will hold the g (may be **NULL**)

gnutls\_datum\_t \* y

will hold the y (may be **NULL**)

**DESCRIPTION**

This function will export the DSA public key's parameters found in the given certificate. The new parameters will be allocated using **gnutls\_malloc()** and will be stored in the appropriate datum.

This function allows for **NULL** parameters since 3.4.1.

**RETURNS**

**GNUTLS\_E\_SUCCESS** on success, otherwise a negative error code.

**SINCE**

3.3.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>