

NAME

gnutls_pubkey_export_dsa_raw2 - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_export_dsa_raw2(gnutls_pubkey_t key, gnutls_datum_t * p, gnutls_datum_t * q,  
gnutls_datum_t * g, gnutls_datum_t * y, unsigned flags);
```

ARGUMENTS

gnutls_pubkey_t key

Holds the public key

gnutls_datum_t * p

will hold the p (may be **NULL**)

gnutls_datum_t * q

will hold the q (may be **NULL**)

gnutls_datum_t * g

will hold the g (may be **NULL**)

gnutls_datum_t * y

will hold the y (may be **NULL**)

unsigned flags

flags from **gnutls_abstract_export_flags_t**

DESCRIPTION

This function will export the DSA public key's parameters found in the given certificate. The new parameters will be allocated using **gnutls_malloc()** and will be stored in the appropriate datum.

This function allows for **NULL** parameters since 3.4.1.

RETURNS

GNUTLS_E_SUCCESS on success, otherwise a negative error code.

SINCE

3.6.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>