

NAME

gnutls_pubkey_get_openpgp_key_id - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_get_openpgp_key_id(gnutls_pubkey_t key, unsigned int flags, unsigned char *  
output_data, size_t * output_data_size, unsigned int * subkey);
```

ARGUMENTS

gnutls_pubkey_t key

Holds the public key

unsigned int flags

should be one of the flags from **gnutls_keyid_flags_t**

unsigned char * output_data

will contain the key ID

size_t * output_data_size

holds the size of output_data (and will be replaced by the actual size of parameters)

unsigned int * subkey

ignored

DESCRIPTION

This function is no-op.

RETURNS

GNUTLS_E_UNIMPLEMENTED_FEATURE.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>