

NAME

gnutls_pubkey_import_ecc_raw - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_import_ecc_raw(gnutls_pubkey_t key, gnutls_ecc_curve_t curve, const
gnutls_datum_t * x, const gnutls_datum_t * y);
```

ARGUMENTS

gnutls_pubkey_t key

The structure to store the parsed key

gnutls_ecc_curve_t curve

holds the curve

const gnutls_datum_t * x

holds the x-coordinate

const gnutls_datum_t * y

holds the y-coordinate

DESCRIPTION

This function will convert the given elliptic curve parameters to a **gnutls_pubkey_t**. The output will be stored in *key*.

In EdDSA curves the *y* parameter should be **NULL** and the *x* parameter must be the value in the native format for the curve.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>