

**NAME**

gnutls\_pubkey\_import\_openpgp\_raw - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_import_openpgp_raw(gnutls_pubkey_t pkey, const gnutls_datum_t * data,
                                     gnutls_openpgp_crt_fmt_t      format, const gnutls_openpgp_keyid_t      keyid, unsigned int flags);
```

**ARGUMENTS**

gnutls\_pubkey\_t pkey

The public key

const gnutls\_datum\_t \* data

The public key data to be imported

gnutls\_openpgp\_crt\_fmt\_t format

The format of the public key

const gnutls\_openpgp\_keyid\_t keyid

The key id to use (optional)

unsigned int flags

Should be zero

**DESCRIPTION**

This function is no-op.

**RETURNS**

**GNUTLS\_E\_UNIMPLEMENTED\_FEATURE.**

**SINCE**

3.1.3

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>