

NAME

gnutls_pubkey_import_privkey - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_import_privkey(gnutls_pubkey_t key, gnutls_privkey_t pkey, unsigned int usage,
unsigned int flags);
```

ARGUMENTS

gnutls_pubkey_t key

The public key

gnutls_privkey_t pkey

The private key

unsigned int usage

GNUTLS_KEY_* key usage flags.

unsigned int flags

should be zero

DESCRIPTION

Imports the public key from a private. This function will import the given public key to the abstract **gnutls_pubkey_t** type.

Note that in certain keys this operation may not be possible, e.g., in other than RSA PKCS11 keys.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>