

## NAME

gnutls\_pubkey\_set\_key\_usage - API function

## SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_set_key_usage(gnutls_pubkey_t key, unsigned int usage);
```

## ARGUMENTS

gnutls\_pubkey\_t key

a certificate of type **gnutls\_x509\_crt\_t**

unsigned int usage

an ORed sequence of the GNUTLS\_KEY\_\* elements.

## DESCRIPTION

This function will set the key usage flags of the public key. This is only useful if the key is to be exported to a certificate or certificate request.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

## SINCE

2.12.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>