

NAME

gnutls_record_can_use_length_hiding - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
unsigned gnutls_record_can_use_length_hiding(gnutls_session_t session);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

DESCRIPTION

If the session supports length-hiding padding, you can invoke **gnutls_record_send_range()** to send a message whose length is hidden in the given range. If the session does not support length hiding padding, you can use the standard **gnutls_record_send()** function, or **gnutls_record_send_range()** making sure that the range is the same as the length of the message you are trying to send.

RETURNS

true (1) if the current session supports length-hiding padding, false (0) if the current session does not.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>