

gnutls_session_enable_compatibility_mode(3) gnutls gnutls_session_enable_compatibility_mode(3)

NAME

gnutls_session_enable_compatibility_mode - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_session_enable_compatibility_mode(gnutls_session_t session);
```

ARGUMENTS

gnutls_session_t session
is a **gnutls_session_t** type.

DESCRIPTION

This function can be used to disable certain (security) features in TLS in order to maintain maximum compatibility with buggy clients. Because several trade-offs with security are enabled, if required they will be reported through the audit subsystem.

Normally only servers that require maximum compatibility with everything out there, need to call this function.

Note that this function must be called after any call to `gnutls_priority` functions.

SINCE

2.1.4

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>