

**NAME**

gnutls\_session\_set\_id - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
int gnutls_session_set_id(gnutls_session_t session, const gnutls_datum_t * sid);
```

**ARGUMENTS**

gnutls\_session\_t session

is a **gnutls\_session\_t** type.

const gnutls\_datum\_t \* sid

the session identifier

**DESCRIPTION**

This function sets the session ID to be used in a client hello. This is a function intended for exceptional uses. Do not use this function unless you are implementing a custom protocol.

To set session resumption parameters use **gnutls\_session\_set\_data()** instead.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise an error code is returned.

**SINCE**

3.2.1

**REPORTING BUGS**

Report bugs to <[bugs@gnutls.org](mailto:bugs@gnutls.org)>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls\_session\_set\_id(3)

gnutls

gnutls\_session\_set\_id(3)

<https://www.gnutls.org/manual/>

gnutls

3.7.9

gnutls\_session\_set\_id(3)