

**NAME**

gnutls\_session\_ticket\_send - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
int gnutls_session_ticket_send(gnutls_session_t session, unsigned nr, unsigned flags);
```

**ARGUMENTS**

gnutls\_session\_t session

is a **gnutls\_session\_t** type.

unsigned nr the number of tickets to send

unsigned flags

must be zero

**DESCRIPTION**

Sends a fresh session ticket to the peer. This is relevant only in server side under TLS1.3. This function may also return **GNUTLS\_E\_AGAIN** or **GNUTLS\_E\_INTERRUPTED** and in that case it must be called again.

**RETURNS**

**GNUTLS\_E\_SUCCESS** on success, or a negative error code.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>