

NAME

gnutls_sign_get_pk_algorithm - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
gnutls_pk_algorithm_t gnutls_sign_get_pk_algorithm(gnutls_sign_algorithm_t sign);
```

ARGUMENTS

gnutls_sign_algorithm_t *sign*
is a signature algorithm

DESCRIPTION

This function returns the public key algorithm corresponding to the given signature algorithms. Note that there may be multiple public key algorithms supporting a particular signature type; when dealing with such algorithms use instead **gnutls_sign_supports_pk_algorithm()**.

SINCE

3.1.1

RETURNS

return a **gnutls_pk_algorithm_t** value, or **GNUTLS_PK_UNKNOWN** on error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>